

# Contents

List of Symbols . . . . .	IX
<b>Introduction</b>	<b>1</b>
<b>I Experimental Results and Cell Model Verification</b>	<b>3</b>
<b>1 Introduction to Part 1</b>	<b>5</b>
<b>2 Electrical Mismatching of Solar Cells</b>	<b>7</b>
2.1 I-V Curve and Important Cell/Module Parameters . . . . .	7
2.2 Series and Parallel Electrical Connections . . . . .	9
2.3 Good and Faulty I-V Curves . . . . .	11
2.4 Summary . . . . .	14
<b>3 Physics of Reverse Biased Solar Cells</b>	<b>15</b>
3.1 p-n Junction at Thermal Equilibrium . . . . .	16
3.2 Applied Forward and Reverse Bias . . . . .	17
3.2.1 Applied Forward Bias, $V = V_F$ . . . . .	19
3.2.2 Applied Reverse Bias, $V = -V_R$ . . . . .	21
3.2.3 Width of Space-Charge Region, $W$ . . . . .	22
3.2.4 Summary of Ideal Solar Cell Model in Reverse Bias . . . . .	22
3.3 Reverse Dark Current for a Solar Cell . . . . .	22
3.3.1 Diode Saturation Current Component, $I_{ds}$ . . . . .	24
3.3.2 Generation Current Component, $I_{gen}$ . . . . .	25
3.3.3 Tunneling Current, $I_{tun}$ . . . . .	28
3.3.4 Ohmic Leakage Current, $I_{sh}$ . . . . .	30
3.3.5 Summary of Reverse Current Components . . . . .	30
3.4 Junction Breakdown and Hot Spots . . . . .	31
3.4.1 Tunneling or Zener Breakdown . . . . .	32
3.4.2 Avalanche Breakdown . . . . .	32
3.4.3 Hot Spots in Reverse Biased Solar Cells . . . . .	35
3.4.4 Summary of Breakdown Mechanisms, Hot Spots . . . . .	35
3.5 Illuminated Characteristics . . . . .	36

3.6	Standard Mathematical Models . . . . .	37
3.6.1	Two-Diode Equation . . . . .	38
3.6.2	Bishop's Model for Avalanche Breakdown . . . . .	39
3.6.3	Series and Shunt Resistances $R_{ser}$ , $R_{sh}$ . . . . .	40
3.6.4	Summary of Diode Models . . . . .	41
<b>4</b>	<b>Measured I-V Curves in Reverse Bias</b>	<b>43</b>
4.1	Experimental Set-Up and Procedure . . . . .	44
4.2	Analysis of Reverse I-V Characteristics for $10 \times 10 \text{ cm}^2$ mc-Si Solar Cells . . . . .	46
4.2.1	Variation of Reverse Characteristics . . . . .	47
4.2.2	Temperature Dependence . . . . .	48
4.2.3	Irradiation Dependence . . . . .	50
4.2.4	Dominant Reverse Bias Current Component . . . . .	52
4.2.5	Results of Parameter Fitting and Analysis . . . . .	54
4.2.6	Multi-Slope I-V Characteristics . . . . .	55
4.3	Analysis of Reverse I-V Characteristics for $10 \times 10 \text{ cm}^2$ m-Si Solar Cells . . . . .	56
4.4	Analysis of Reverse I-V Characteristics for $2 \times 2 \text{ cm}^2$ mc-Si Silso Solar Cells . . . . .	58
4.4.1	Irradiation Dependence . . . . .	61
4.4.2	Exceptional ISE Silso Cell . . . . .	61
4.5	Degradation Effects Due to Reverse Bias Stress . . . . .	63
4.6	Summary of Experimental Analysis . . . . .	65
<b>5</b>	<b>Partial Shading of Solar Cells</b>	<b>67</b>
5.1	Theory . . . . .	68
5.2	Experimental Set-Up . . . . .	69
5.3	Experimental Results . . . . .	71
5.3.1	Partial Shading Effect for Reverse Characteristics . . . . .	76
5.4	Shading Orientation . . . . .	78
5.5	Shaded Cell in Modules . . . . .	79
5.5.1	Experimental Set-Up . . . . .	80
5.5.2	Experimental Results . . . . .	81
5.5.3	Different Reverse Characteristics of Solar Cells in a Single Module . . . . .	84
5.6	Summary from Partial Shading Analysis . . . . .	85
<b>6</b>	<b>Temperature Distribution and Hot Spots</b>	<b>87</b>
6.1	Introduction . . . . .	87
6.2	IR Camera Experiments . . . . .	88
6.2.1	Principle of IR Camera . . . . .	88
6.2.2	Preparatory Experiments . . . . .	89

6.3	Experimental Set-Up . . . . .	92
6.4	Experimental Results . . . . .	93
6.4.1	Reproducibility of Experimental Results . . . . .	93
6.4.2	Temperature Distribution Measurements on $10 \times 10 \text{ cm}^2$ mc-Si Cells . . . . .	94
6.4.3	Temperature Distribution Measurements on nearly Round mc-Si Cells . . . . .	97
6.4.4	Temperature Distribution Measurements on $10 \times 10 \text{ cm}^2$ m-Si Cells . . . . .	99
6.5	Summary of Hot Spot Measurements . . . . .	101
<b>7</b>	<b>Conclusions for Part 1</b>	<b>103</b>
<b>II</b>	<b>Description of Simulation Package and Analysis</b>	<b>105</b>
<b>8</b>	<b>Introduction to Part 2</b>	<b>107</b>
<b>9</b>	<b>Simulation Package, PVPACK</b>	<b>109</b>
9.1	Irradiation Distribution Calculations for PV Arrays on Buildings .	112
9.1.1	RADIANCE, an image-oriented raytracing technique . . . .	113
9.1.2	Weather-Dependent Irradiation Distribution . . . . .	114
9.2	Spectral Considerations . . . . .	115
9.2.1	AM1.5 Spectrum . . . . .	116
9.3	Visual Preliminary View of Shading . . . . .	117
9.4	Effective Irradiation . . . . .	118
9.5	Partial Shading of Solar Cells . . . . .	119
9.6	PV Array Simulator, PVIRR . . . . .	119
9.6.1	PV Array Energy Output and Operating Strategy . . . . .	120
9.6.2	Hot Spot Temperatures and Dissipated Power . . . . .	120
9.7	Speed of PVPACK . . . . .	121
9.8	Summary of Package Description . . . . .	122
<b>10</b>	<b>Climatic Factors and Tilt Angles</b>	<b>123</b>
10.1	Direct and Diffuse Irradiation . . . . .	124
10.2	Tilt Angle and Orientation . . . . .	127
10.3	Layout of PV Array . . . . .	130
10.4	PV Energy at Different Tilt Angles . . . . .	131
10.5	Summary . . . . .	134
<b>11</b>	<b>Case A: PV-Shading Elements</b>	<b>135</b>
11.1	Integration Strategy for Case A . . . . .	137
11.2	Freiburg: Simulation Results for Varying $\beta$ and $D$ . . . . .	139
11.2.1	Irradiation Distribution on an Unshaded and Shaded Module	140

11.2.2	Annual Energy Output and Shading Losses . . . . .	142
11.3	Cell Temperature Increase during Shading . . . . .	147
11.3.1	Effect of Integrated Diodes on Energy Output . . . . .	149
11.4	Different Facade Materials . . . . .	150
11.5	Horizontally Oriented PV Modules . . . . .	151
11.6	Vertical Facade with 2 Overhangs . . . . .	154
11.7	Fresno: Simulation Results for Varying $\beta$ and $D$ . . . . .	157
11.8	Summary of Case A . . . . .	161
<b>12</b>	<b>Case B: Building Facade Shaded by Overhang</b>	<b>163</b>
12.1	Freiburg: Simulation Results for Varying $L$ and $A$ . . . . .	165
12.2	Monthly Shading Losses . . . . .	167
12.3	Vertically Oriented Modules . . . . .	169
12.4	Summary of Case B . . . . .	171
<b>13</b>	<b>Simulation Results for Cases C and D</b>	<b>173</b>
13.1	Case C: South-facing Facade with Framework . . . . .	173
13.1.1	Simulation Results for Varying $X$ and $B$ , Freiburg . . . . .	175
13.2	Case D: Facade Shaded by Wingwall . . . . .	179
13.2.1	Simulation Results for Varying $\gamma$ and $Z$ . . . . .	180
13.3	Summary of Cases C and D . . . . .	181
<b>14</b>	<b>Conclusions</b>	<b>183</b>
<b>A</b>	<b>Solar and Semiconductor Sign Convention</b>	<b>185</b>
	<b>References</b>	<b>187</b>